



STAND-ON SKID STEERS

BUILT TO OUTPERFORM



		SK600	SK800	SK900	SK1050	SK1550	SK3000
DIMENSIONS	Operating height, max std. bucket	103 in 2.63 m	105 in 2.67 m	105 in 2.67 m	105 in 2.67 m	128.4 in 3.3 m	152.6 in 3.87 m
	Overall height of machine	54 in 1.39 m	57 in 1.45 m	57 in 1.45 m	57 in 1.45 m	58.5 in 1.45 m	64.6 in 1.64 m
	Overall length of machine, std. bucket	105 in 2.67 m	105 in 2.67 m	105 in 2.67 m	105 in 2.67 m	124.2 in 3.16 m	137.6 in 3.49 m
	Hinge pin height, max	76 in 1.93 m	83 in 2.10 m	83 in 2.10 m	83 in 2.10 m	94.5 in 2.4 m	118 in 2.99 m
	Wheelbase/track length	36 in 925 mm	43 in 1.09 m	43 in 1.09 m	43 in 1.09 m	50.6 in 1.29 m	51.5 in 1.31 m
	Machine width (min/max)	33.5 in 850 mm	36/42 in 0.914/1.06 m	36/42 in 0.914/1.06 m	36/42 in 0.914/1.06 m	46.6 in 1.18 m	57.5 in 1.46 m
	Ground clearance, min						
	Center	8.5 in 216 mm	8.9 in 226 mm	8.9 in 226 mm	7.4 in 188 mm	9.1 in 231.1 mm	10.4 in 264.4 mm
	Side	4 in 102 mm	3.7 in 94 mm	3.7 in 94 mm	3.7 in 94 mm	4.7 in 119.4 mm	8.1 in 205.7 mm
	Machine weight (no attachment, fluids full)	2,418 lb 1096 kg	2,920 lb 1324 kg	3,190 lb 1447 kg	3,435 lb 1558 kg	3,990 lb 1810 kg	7,600 lb 3447 kg
	Rated operating capacity, 35% of tipping capacity	600 lb 272 kg	911 lb 413 kg	932 lb 422 kg	1,062 lb 482 kg	1,558 lb 707 kg	3,102 lb 1407 kg
	Tipping capacity	1,725 lb 782 kg	2,605 lb 1182 kg	2,665 lb 1208 kg	3,035 lb 1377 kg	4,450 lb 2019 kg	8,863 lb 4020 kg
POWER	Engine	Kubota® D902-E4B	Kubota® D1105	Yanmar® 3TNV80FT	Yanmar® 3TNV88C	Yanmar® 3TNV86CT	Yanmar® 4TNV86CT
	Fuel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
	Gross power rating (SAE J1995)	24.8 hp 18.5 kW	24.8 hp 18.5 kW	24.8 hp 18.5 kW	37 hp 27.5 kW	43.5 hp 32.4 kW	58.9 hp 43.9 kW
	Emissions compliance	EPA Tier 4 EU Stage IIIA	EPA Tier 4	EPA Tier 4 Final EU Stage V	EPA Tier 4 EU Stage IIIA	EPA Tier 4 Final EU Stage IIIA	EPA Tier 4 Final EU Stage V
	Rated speed	3,600 rpm	3,000 rpm	2,600 rpm	3,000 rpm	3,000 rpm	3,000 rpm
OPERATION	Ground drive speed	4.1 mph 6.6 km/h	4.3 mph 6.9 km/h	4.0 mph 6.4 km/h	4.7 mph 7.6 km/h	4.7 mph 7.6 km/h	5.8 mph 7.6 km/h
HYDRAULIC SYSTEM	Double gear pump						
	Flow rate at 100% efficiency	12.6 gpm 47.7 l/min	11.9 gpm 45 l/min	12.0 gpm 45.4 l/min	14.1 gpm 53.4 l/min	17.4 gpm 65.9 l/min	24.0 gpm 90.8 l/min
	Pressure	3,000 psi 207 bar	3,000 psi 207 bar	3,000 psi 207 bar	3,625 psi 250 bar	3,700 psi 255 bar	4,000 psi 250 bar